



Delta 2000 18% High Speed Floor Finish Sellador / Capa De Alta Brillo

Description

This product is a simplified floor finish that provides the end user with an extremely tough and durable high gloss finish. It is formulated to respond to low, high, and ultra high speed maintenance techniques and is self-sealing so fewer products are needed to complete the job.

Directions



Wear safety glasses & gloves Usar gafas de seguridad y guantes

Apply 3 - 5 coats evenly with clean mop Aplique uniformemente 3-5 capas con una mopa de limpia

Allow to dry 30 - 45 minutes between coats Deje secar 30-45 minutos entre una capa y otra

Completely dry before applying next coat Seque completamente antes de aplicar la capa siguiente

Allow at least 24 hours before use Deje pasar al menos 24 horas antes del uso

For detailed instructions and safety information, please review container label and SDS.



Features

- Durable
- High Gloss
- Economical

Applications

Recommended for areas where higher maintenance is desired:

- Schools and hospitals
- Airports and offices

Specifications

Color	White
Fragrance	Characteristic
pH Range	8.0 - 8.5
Dilution	RTU
Coverage	. 2000 sq ft/diluted gal

Packaging

ITEM #	SIZE
BSL15180005	5 Gallons
BSL15180007	2/2.5 Gallons



Contact your Account Representative for more information

140 Private Brand Way, Athens, TN 37303 | mybrightsolutions.com In case of emergency call Infotrac 800.535.5053 © 2018 Midlab, Inc. All right reserved. PLUS Label System is a trademark of Midlab, Inc.Patent Pending.