

Safety Data Sheet

Issue Date 01-Sept-2011

Revision/Review Date: 10-Aug-2018

Version 1.1

1. IDENTIFICATION

Product Identifier

Product Name Bright Solutions Dynamite

Other Means of Identification

Product Code BSL11060005

Recommended use of the Chemical and Restrictions on Use

Recommended Use Floor stripper. For industrial use.

Details of the Supplier of the Safety Data Sheet

Bright Solutions
140 Private Brand Way
Athens, TN 37303

Emergency Telephone Number

Company Phone Number Phone: 1-800-467-6294
Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Colorless

Physical State Liquid

Odor None

Classification

Acute toxicity - Inhalation (Vapors)	Category 4
Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 1
Corrosive to metals	Category 1

Hazards Not Otherwise Classified (HNOC)

May be harmful if swallowed

Signal Word

Danger



Hazard Statements

Harmful if inhaled.
Causes severe skin burns and eye damage.
May be corrosive to metals.

Precautionary Statements - Prevention

Use only outdoors or in a well-ventilated area.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wash face, hands and any exposed skin thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.
Keep only in original container.

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician.
IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.
SPECIFIC TREATMENT: Remove from exposure and treat symptoms.

Precautionary Statements - Storage

Store locked up.
Store in corrosive container with a resistant inner liner.

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant.

Unknown Acute Toxicity

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Water	7732-18-5	60-100
Ethylene Glycol n-Butyl Ether	111-76-2	10-30
Monoethanolamine	141-43-5	5-10
Potassium Hydroxide	1310-58-3	1-5
Sodium Xylene Sulfonate	1300-72-7	1-5
Nonylphenoxypolyethoxyethanol	68412-54-4	0.5-1.5

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

First Aid Measures

- Eye Contact** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.
- Skin Contact** IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse.
- Inhalation** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician.
- Ingestion** Never give anything by mouth to an unconscious person. Clean mouth with water and drink afterwards plenty of water. Do not induce vomiting. Call a physician immediately.

Most Important Symptoms and Effects

- Symptoms** Causes severe skin burns and eye damage. Prolonged or repeated exposure can remove natural skin oils and may produce irritation. Chronic exposure may cause liver, kidney and/or blood disorders.

Indication of any Immediate Medical Attention and Special Treatment Needed

- Notes to Physician** Treat symptomatically. May aggravate pre-existing skin disorders and pulmonary diseases.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water spray (fog). Carbon dioxide (CO2). Water. Foam.

Unsuitable Extinguishing Media

Not determined.

Specific Hazards Arising from the Chemical

None known.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

- Personal Precautions** Wear protective clothing as described in Section 8 of this safety data sheet.
- Environmental Precautions** Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information. See Section 13, Disposal Considerations, for additional information. See Section 12 for additional Ecological Information.

Methods and Material for Containment and Cleaning Up

- Methods for Containment** Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
- Methods for Clean-Up** Contain and collect with an inert absorbent and place into an appropriate container for disposal. Dilute remaining residue with water and neutralize with dilute acetic acid (vinegar).

7. HANDLING AND STORAGE

Precautions for Safe Handling

- Advice on Safe Handling** Handle in accordance with good industrial hygiene and safety practice. Use personal protection recommended in Section 8. For industrial and commercial use only. Avoid contact with skin, eyes or clothing. Wash face, hands, and any exposed skin thoroughly after handling. Take off all contaminated clothing and wash before reuse. Do not breathe dust/fume/gas/mist/vapors/spray.

Conditions for Safe Storage, including any Incompatibilities

- Storage Conditions** Keep container tightly closed and store in a cool, dry and well-ventilated place. Protect from freezing. Keep out of the reach of children. Store locked up.
- Incompatible Materials** Acids. Oxidizing agents. Uncontrolled contact with water.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ethylene Glycol n-Butyl Ether 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³
Monoethanolamine 141-43-5	STEL: 6 ppm TWA: 3 ppm	TWA: 3 ppm TWA: 6 mg/m ³ (vacated) TWA: 3 ppm (vacated) TWA: 8 mg/m ³ (vacated) STEL: 6 ppm (vacated) STEL: 15 mg/m ³	IDLH: 30 ppm TWA: 3 ppm TWA: 8 mg/m ³ STEL: 6 ppm STEL: 15 mg/m ³
Potassium Hydroxide 1310-58-3	Ceiling: 2 mg/m ³	(vacated) Ceiling: 2 mg/m ³	Ceiling: 2 mg/m ³

Appropriate Engineering Controls

- Engineering Controls** Apply technical measures to comply with the occupational exposure limits. Ensure adequate ventilation, especially in confined areas. Good general room ventilation (equivalent to outdoors) should be adequate under normal conditions. Eyewash

stations. Showers.

Individual Protection Measures, such as Personal Protective Equipment

Eye/Face Protection	Use chemical splash goggles or glasses as necessary to prevent contact.
Skin and Body Protection	Protective chemical impervious gloves of butyl rubber, nitrile rubber or PVC, chemical resistant suit and boots.
Respiratory Protection	Ensure adequate ventilation, especially in confined areas. In case of inadequate ventilation wear respiratory protection.
General Hygiene Considerations	Handle in accordance with good industrial hygiene and safety practice. Wash face, hands and any exposed skin thoroughly after handling. Wash contaminated clothing before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES**Information on Basic Physical and Chemical Properties**

Physical State	Liquid	Odor	None
Appearance	Clear	Odor Threshold	Not determined
Color	Colorless		
Property	Values	Remarks • Method	
pH	>13.0		
Melting Point/Freezing Point	Not known		
Boiling Point/Boiling Range	~ 101 °C / ~214 °F		
Flash Point	Not applicable		
Evaporation Rate	Not determined		
Flammability (Solid, Gas)	Liquid-not applicable		
Upper Flammability Limits	Not applicable		
Lower Flammability Limit	Not applicable		
Vapor Pressure	Not determined		
Vapor Density	Not determined		
Specific Gravity	1.02		
Water Solubility	Completely soluble	@ 25 °C (77 °F)	
Solubility in other solvents	Not determined		
Partition Coefficient	Not determined		
Auto-ignition Temperature	Not determined		
Decomposition Temperature	Not determined		
Kinematic Viscosity	Not determined		
Dynamic Viscosity	Not determined		
Explosive Properties	Not determined		
Oxidizing Properties	Not determined		

10. STABILITY AND REACTIVITY**Reactivity**

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to Avoid

Keep out of reach of children. Keep from freezing.

Incompatible Materials

Acids. Oxidizing agents. Uncontrolled contact with water.

Hazardous Decomposition Products

Normal products of combustion.

11. TOXICOLOGICAL INFORMATION**Information on Likely Routes of Exposure****Product Information****Eye Contact** Causes severe eye damage.**Skin Contact** Causes severe skin burns.**Inhalation** Harmful if inhaled.**Ingestion** May be harmful if swallowed.**Component Information**

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Ethylene Glycol n-Butyl Ether 111-76-2	= 470 mg/kg (Rat)	= 2270 mg/kg (Rat) = 220 mg/kg (Rabbit)	= 2.21 mg/L (Rat) 4 h = 450 ppm (Rat) 4 h
Monoethanolamine 141-43-5	= 1720 mg/kg (Rat)	= 1 mL/kg (Rabbit) = 1025 mg/kg (Rabbit)	-
Potassium Hydroxide 1310-58-3	= 214 mg/kg (Rat)	-	-
Sodium Xylene Sulfonate 1300-72-7	= 7200 mg/kg (Rat)	-	-

Information on Physical, Chemical and Toxicological Effects**Symptoms** Please see section 4 of this SDS for symptoms.**Delayed and Immediate Effects as well as Chronic Effects from Short and Long-Term Exposure****Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen. However, the product as a whole has not been tested. Group 3 IARC components are "not classifiable as human carcinogens".

Chemical Name	ACGIH	IARC	NTP	OSHA
Ethylene Glycol n-Butyl Ether 111-76-2	A3	Group 3		

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 3 IARC components are "not classifiable as human carcinogens"

Chronic toxicity Chronic exposure may cause liver, kidney and/or blood disorders.**Numerical Measures of Toxicity**

Not determined

Unknown Acute Toxicity

None known.

12. ECOLOGICAL INFORMATION**Ecotoxicity**

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea

Bright Solutions Dynamite

Revision/Review Date: 10-Aug-2018

Ethylene Glycol n-Butyl Ether 111-76-2	-	1490: 96 h Lepomis macrochirus mg/L LC50 static 2950: 96 h Lepomis macrochirus mg/L LC50	-	1698 - 1940: 24 h Daphnia magna mg/L EC50 1000: 48 h Daphnia magna mg/L EC50
Monoethanolamine 141-43-5	15: 72 h Desmodemus subspicatus mg/L EC50	227: 96 h Pimephales promelas mg/L LC50 flow-through 3684: 96 h Brachydanio rerio mg/L LC50 static 300 - 1000: 96 h Lepomis macrochirus mg/L LC50 static 114 - 196: 96 h Oncorhynchus mykiss mg/L LC50 static 200: 96 h Oncorhynchus mykiss mg/L LC50 flow-through	-	65: 48 h Daphnia magna mg/L EC50
Potassium Hydroxide 1310-58-3	-	80: 96 h Gambusia affinis mg/L LC50 static	-	-

Persistence/Degradability

Not determined

Bioaccumulation

Not determined

Mobility

Chemical Name	Partition Coefficient
Ethylene Glycol n-Butyl Ether 111-76-2	0.81
Monoethanolamine 141-43-5	-1.91
Potassium Hydroxide 1310-58-3	0.83

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS**Waste Treatment Methods****Disposal of Wastes**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Potassium Hydroxide 1310-58-3	Toxic Corrosive

14. TRANSPORT INFORMATION**Note**

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances. Based on package size, product may be eligible for limited quantity exception.

DOT

UN/ID No

UN1760, Corrosive Liquid, NOS (Containing Monoethanolamine), 8, PG II

IATA**IMDG****15. REGULATORY INFORMATION****International Inventories**

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Potassium Hydroxide 1310-58-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Reactive Hazard	Yes

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Ethylene Glycol n-Butyl Ether	111-76-2	10-30	1.0

CWA (Clean Water Act)


This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Potassium Hydroxide 1310-58-3	1000 lb			X

US State Regulations

California Proposition 65

This product contains a chemical known to the State of California to cause cancer.

 **WARNING:** This product can expose you to Diethanolamine, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

U.S. State Right-to-Know Regulations

Chemical Name	State List
Ethylene Glycol n-Butyl Ether 111-76-2	NJ, MA, PA
Monoethanolamine 141-43-5	NJ, MA, PA
Potassium Hydroxide 1310-58-3	NJ, MA, PA

AZ – Arizona Ambient Air Quality Guidelines
 CT – Connecticut Hazardous Air Pollutants
 CA – California Director’s List of Hazardous Substances
 CAP65 – California Prop 65
 FL – Florida Substances List
 ID – Idaho Non-Carcinogen Toxic Air Pollutants

IL – Illinois Toxic Air Contaminate- Carcinogenic
 MA – Massachusetts Right to Know List
 MN – Minnesota Hazardous Substances List
 NJ – New Jersey Right to Know List
 PA – Pennsylvania Right to Know List
 RI – Rhode Island Hazardous Substances List

16. OTHER INFORMATION

HMIS

determined
Health Hazards
3

Flammability
Not determined
Flammability
0

Instability
Not determined
Physical Hazards
0

Special Hazards
Not determined
Personal Protection
Not determined

Issue Date 01-Sept-2011
Revision/Review Date: 10-Aug-2018
Revision Note Version 1.1 Updated Section 15

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Keep Out of Reach of Children. For Industrial and Institutional Use Only.

*Denotes changes from last version.

End of Safety Data Sheet